

XR7[®] RIDGELINE

Ridgeline XR7

ABS/PC material // 6-point ratchet suspension // Swinging hinge points // Soft 4-point chin strap with breakaway // Adjustable height and angle options for the suspension // Easy to grasp knob adjusts the suspension from 6½ to 8 head size // Packaged with reflective stickers// Custom imprinting available

- HP76110 White
- HP76113 Slate Gray
- HP76117 Black Graphite
- HP76130 Yellow
- HP76131 Hi-vis Lime
- HP76160 Blue

Ridgeline XR7 passes ANSI Z89.1-2014 Type I, Class E and CE EN 397:2012 +A1:2012.



XR7[®] RIDGELINE

Ridgeline XR7

STANDARDS

ANSI Z89.1-2014 Type 1, Class E

CE EN 397:2012 +A1:2012

SPECS

HAT

Shell ABS/PC — Acrylonitrile butadiene styrene and polycarbonate

FOAM

Crown EPS — Expanded polystyrene

SUSPENSION PIECES

Plastic LDPE — Low-density polyethylene

Headband Lycra fabric wrapped over sponge

Back cushion EVA — Ethylene vinyl acetate

Pyramex Logo Portion Adhesive sticker

CHIN STRAP PIECES

Strap Terylene

Under Chin Material PU — Polyurethane

Buckle POM — Polyoxymethylene

WEIGHTS AND MEASURES

Complete Hat Weight 464G

Shell thickness 3.8mm

FEATURES

- ABS/PC blend offers superior strength and higher heat resistance
- 6-point ratchet suspension with option to easily interchange to a 4-point
- 4-point chin strap with breakaway feature
- Soft PU strap comfortably rests under the chin and secures the hat
- 3 adjustable height options for the suspension
- 2 settings to adjust the wearing angle
- Adjustable knob allows easy adjustment of suspension from size 6 1/2 to 8

MARKINGS

- Types: Type 1 offers protection to the top of the head
- Classes: Class E (electrical) rated for 20,000 volts
- LT: Provides protection at low temperatures -22°F
- HT: Provides protection at high temperatures 140°F
- Date code: Indicates month and year when the shell was molded — does not indicate service life



PRODUCT GUIDELINES

- Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use
- Never alter or modify the shell or suspension system
- Inspect the hard hat each time before use and replace if there is any sign of damage
- Replace hard hat after it receives a considerable impact
- Accessories such as liners have not been tested to the requirement of this standard
- Clean only with mild soap and lukewarm water
- Store hard hat in a clean, dry place that is out of direct sunlight
- Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat
- Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage

Ridgeline XR7 image shown with CM6010, HHABCMR, and S1110, sold separately.